

AVZ1009



H.265 5MP PENTABRID 8CH XVR

FEATURES


H.265 Compression Technology

- ❖ The recording capacity is greatly enhanced as well as bandwidth saving for better efficiency and performance than the systems employing other compression formats



Scenario Customization

- ❖ Allows you to customize a series of actions which will be run automatically after the specified event occurs. There are several scenario templates for you to choose when and what to do after a specific event occurs.



Free P2P Cloud EaZy Networking

- ❖ Cloud EaZy Networking available to connect this device to Internet automatically in three steps with our free mobile app, EagleEyes.
- ❖ The "Buddy" feature to share the device access permission to other people.
- ❖ Device login / out notifications are reported.

Push Video & Push Status - Active Event Notification with EagleEyes App


- ❖ Push Video to send instant notifications for an alarm event when an alarm device is connected to the recorder or the camera which supports external alarm device connection.
- ❖ Push Status to send instant notifications for system events, such as video loss or HDD data removal.

Pentabrid Video Input

- ❖ 8 channels of IP / TVI / CVI / Analog HD / 960H video input + one more channel of IP video input
- ❖ Up to 5MP display & recording


Event Pop-up / Preview

- ❖ All events are listed on the right panel with corresponding event icons for you to quickly recognize the event type. The most current one will flash to catch your attention. Click one event and you're able to preview the footage with pre-alarm images.



Spot Monitor

- ❖ In addition to the main display via the HDMI output, you can assign a secondary display to show live view, call monitor or event monitor.



SPECIFICATIONS

▼ Video

Video System	NTSC / PAL (auto detection)	
Video Compression Format	H.265	
Video Signal	IP / TVI / CVI / Analog HD / 960H	
Video Input	8 pentabrid channels (IP / TVI / CVI / Analog HD / 960H) + 1 IP channel	
Video Input Interface	Analog Mode	Composite video signal 1 Vp-p 75Ω BNC
	IP Mode	Ethernet, 10/100 Base-T
Video Output	BNC	YES (Spot Monitor supported)
	VGA	YES (Spot Monitor supported)
	HDMI	YES (4K2K display)
Video Resolution	Analog Mode	5MP / 5MLITE / 4MP / 4MLITE / FHD (1080P) / HD / 960H / Frame / CIF
	IP Mode	2592 x 1944 / 2048 x 1536 / 1920 x 1080 / 1280 x 720 / 720 x 480 / 352 x 240

▼ Record & Backup

Max. Recording Rate	Analog Mode	Up to 48 IPS @ 5MP Up to 64 IPS @ 4MP Up to 120 IPS @ FHD (1080P)
	IP Mode (9 channels)	UP to 135 IPS @ 2592 x 1944 (5MP) UP to 216 IPS @ 2048 x 1536 (3MP) UP to 270 IPS @ 1920 x 1080
Recording Mode	Manual / Timer / Motion / Alarm / Remote	
Playback Channel	8CH	
Quick Search	Time / Motion / Alarm search mode	
Backup Device	USB 2.0 drive / Network	
Regular Backup	YES	

▼ Audio

Audio Input	4
Audio Output	1 (Mono)

▼ External I/O

RS485	YES
Alarm Input	4
Alarm Output	1

▼ General

Hard Disk Storage	14TB SATA HDD x 1 or external disk array x 1 connected to the recorder via the eSATA interface
SATA Interface	YES
eSATA Interface	Expandable with a SATA to eSATA cable
Image Quality Setting	SUPER BEST / BEST / HIGH / NORMAL
USB Mouse Control	YES
Motion Detection Area	16 × 12 grids per channel
Motion Detection Sensitivity	3 adjustable parameters for accurate detection
Event Notification	Push Video / Push Status / FTP / E-Mail
Event Pop-up & Preview	YES
Scenario Setup	YES
Picture Zoom	2X digital zoom
PTZ Control	YES
Key Lock (Password Protection)	YES
User Level	4 user levels for different access privilege
Video Loss Detection	YES
Camera Title	Supports up to 25 letters

SPECIFICATIONS

▼ General

Video Adjustable	Hue / Saturation / Contrast / Brightness
Date Display Format	YY/MM/DD, DD/MM/YY & MM/DD/YY
Daylight Saving	YES
Power Source (±10%)	12V / 2A
Operating Temperature	10°C ~ 40°C (50°F ~104°F)
Operating Humidity	10% ~ 85%
Dimensions(mm)**	260 x 235.7 x 48
Net Weight (kg)	1.3

▼ Network

Ethernet	10/100 Base-T. Supports remote control and live view via Ethernet
Network Protocol	TCP/IP, PPPOE, DHCP and DDNS

▼ Remote Surveillance from PC

Compatible Operating System	Windows & MAC
Compatible Program	Web Browser: Windows Edge, Microsoft Internet Explorer, Google Chrome, Mozilla Firefox & Safari
	CMS Lite: 32CH central management software for Windows OS
Max. online users	20
Web Transmitting Compression Format	H.265
Network Live Audio	YES
Remote Event Download & Playback	YES

▼ Mobile Surveillance

App	EagleEyes
Compatible Devices	iOS & Android devices
Push Video	YES (8 channels)
Push Status	YES

▼ Others

EaZy Networking	YES
IVA***	YES (4 channels in analog mode)
Spot Monitor Support	YES (BNC / VGA)
DCCS Support	YES
AVTECH Free DDNS service	YES
Privacy Mask	YES
Multiplex Operation	Live display / record / playback / backup / network operations
System Recovery	System auto recovery after power failure
Optional Peripherals	HDMI Matrix (HDM02) / USB Joystick (AVX102) / SATA to eSATA cable (PWSC07F120200)

* The specifications are subject to change without notice.

** Dimensional tolerance: ±5mm

***** Available only when the connected cameras are supported

Rear Panel

