

4k + H.265 + 5MP TVI + 4MPCVI + 4MP AHD + IP + CVBS



- ◆ 7 " IPS touch screen , 1280*800 resolution
- ◆ H.265/H.264, 4K video display via mainstream
- ◆ Built in WIFI , create WIFI hotspot
- ◆ IP discovery , shortcut button, drop-down menu
- ◆ Rapid ONVIF , auto view video and create testing report
- ◆ RJ45 cable TDR test , cable quality test
- ◆ Tester Play: Tester , android version mobile phone, PC display at the same time
- ◆ 5MP TVI , 4MP CVI , 4MP AHD camera test
- ◆ Dual window test , IP & Analog camera test
- ◆ HDMI input& output,support1080p
- ◆ DC12V 2A , DC48V PoE power output
- ◆ Quick office(excel , word , PPT format) doc.
- ◆ UTP cable tester

500124 - 7" IPS Touch Screen IP Camera Tester is designed for maintenance and installation of IP analog, HD coaxial cameras as well as other security equipment. The 1280x800 resolution enables it to display network HD cameras and analog cameras in high resolution. The unit supports many ONVIF PTZ and analog PTZ control. In addition, other functions RJ45 TDR cable test and UTP cable test etc. CCTV installers often need to carry a variety of testing tools to complete their work. Take the all in one camera tester, making working conditions safer and increasing productivity.

VandalVeto®

	Display	7" IPS touch screen ,1280*800 resolution
Video Mode	CVBS	1 channel BNC input & 1 channel BNC looped output, NTSC/PAL (Auto adapt)
		PTZ control ,RS485 control, Baud 600-115200bps,compatible with more than 30 protocols such as PELCO-D/P, Samsung, Panasonic etc.
		CVBS loop test the tester send and receive color bar generator signal , check BNC cable
	IP camera test	IPC test /IPC viewer /Rapid Video/RTSP /ONVIF
		Rapid ONVIF Auto view the video, create ONVIF testing report
		Hik test tool By one key to activate hik camera ,Image test, can modify the user name, password and IP parameters
		Dahua test tool Dahua camera test, modify the user name, password and IP parameters
	IP& CVBS test	IP& CVBS test at the same time ,converter test from analog to digital with dual test window
	Coaxial HD test	5MP TVI camera test,2688x1520p 15fps ,2560x1944P12.5FPS, 2048x1536p 18fps,1080p 25/30fps,720p 25/30/50/60fps,UTC control/ call OSD menu
		4MP CVI camera test,2560x1440P25F/30F ,1080p 25/30fps,720p 25/30/50/60fp, UTC control d call OSD menu
4MP AHD test,2560x1440P15F/25F/30F ,2048x1536p 18/25/30fps, 1080p 25/30fps,720p 25/30fps,UTC control d call OSD menu		
HDMI input	1 channel HDMI input, support 1920x1080P/50/60fps,1920x1080I/25/30/50/60fps1280x720P/25/30/50/60fps, 720x480P/60fps720x576P/60fps, 1280x1024P/60fps 1024x768P/60fps800x600P/60fps	
Zoom Image	4x zoom, to enlarge image, Screen snapshot, record ,save ,view and record and play back	
Analog Video out	color bar generator	Output one channel PAL/NTSC color bar video signal for testing monitor or video cable
HDMI output	1 channel HDMI output, support 1920*1080P	
	12V/2Apower	Output DC12V/2A power out ,supply temporarily power for the camera
Power output	PoE power output	48V PoE power output, max power 24W
	5V/2A power output	USB 5V 2A power output, as a power bank
Cable test	UTP cable test	Test UTP cable connection status and display on the screen. Read the number on the screen
	RJ45 TDR test	Test cable pair status, length, attenuation, reflectivity, impedance, skew etc
Tester Play	screen projection: tester, mobile phone and PC display at the same time (For android version mobile phone)	
Network test	Trace route, Link monitor ,DHCP server, port flashing , Ping test	
Wi-Fi	Built in WIFI,speeds150M,display wireless camera image	
Audio test	1 channel audio signal input, test whether sound normal, 1 channel audio signal, to connect headphone	
Data monitor	Captures and analyzes the command data from controlling device, also can send hexadecimal	
PoE test	Measurement POE switch or PSE power supply voltage and cable connection status	
Drop-down menu	You can select PoE power switch ,IP setting, WLAN switch , HDMI IN functions etc in any interface	
External power supply	DC 12V 2A	

Battery	Built-in 7.4V Lithium polymer battery ,5400mAh
Rechargeable	After charging 5~6 hours, normal working time 10 hours
Operation setting	OSD menu, select your desired language: English, Chinese, Korean, Russian, Italian, French, Polish, Spanish, Japanese etc
Auto off	5-30 (mins)
Working Temp.	-10°C---+50°C
Working Humidity	30%-90%
Dimension/ Weight	240mm x 154mm x 46mm / 620g
A	AHD camera test,4MP AHD camera test,2560x1944P12.5FPS , 2048x1536p 18/25/30fps, 1080p25/30fps,720p 25/30fps ,UTC control/ call OSD menu
H	TVI camera test: 5MP TVI camera test,2688x1520p 15fps ,2560x1944P12.5FPS, 2048x1536p 18fps, 1080p 25/30fps,720p 25/30/50/60fps,UTC control/ call OSD menu
D	CVI camera test : 4MP CVI camera test,2560x1440P25F/30F ,1080p 25/30fps,720p 25/30/50/60fp UTC control d call OSD menu

- 7" IPS touch screen,1280*800 resolution
- **H.264 and H .265 ,4K video display via mainstream**
- **5MP TVI camera test, 2688x1520p 15fps**, 2560x1944P12.5FPS, 2048x1536p 18fps, 1080p 25/30fps, 720p 25/30/50/60fps
- **4MP AHD test, support 2560x1440P15F/25F/30F**, 2048x1536p 18/25/30fps, 1080p 25/30fps, 720p 25/30fps
- **4MP CVI camera test, support 2560x1440P25F/30F**,1080p 25/30fps,720p 25/30/50/60fp,UTC control d call OSD menu, 4xzoom,video record and playback, coaxial PTZ control and call camera OSD menu
- **HDMI signal input**, support 1920x1080P/50/60fps, 920x1080I/25/30/50/60fps, 1280x720P/25/30/50/60fps 720x480P/60fps720x576P/60fps, **1280x1024P/60fps**, display image, record and snapshot
- IP & CVBS camera test, PTZ controller
- Rapid video, just by one key to detect all network cameras and auto display
- Rapid ONVIF, auto log in and display image from the camera, activate Hikvision camera, can create testing report
- IP and analog testing at the same time, converter test from analog to digital with dual test window IP & CVBS
- Screen management, change function's icons order, create new directory
- Shortcut button, drop-down menu, can select PoE power, IP setting, WLAN switch, HDMI IN functions etc. in any interface
- Improvement cable tester: UTP cable, telephone cable etc. order and connectivity test, can save testing report, if special number, need customized
- RJ45 cable TDR test, test cable pair status, length, attenuation, reflectivity, impedance, skew etc.
- Tester Play (screen projection: tester, android version mobile phone and PC display at the same time

VandalVeto®

- **Screen lock**, password lock and pattern lock are optional
- HDMI output, support 1080P
- CVBS loop test, the tester send and receive color bar generator signal, to check BNC cable
- Traffic monitoring of the tester "LAN port", display network port or WIFI connection real-time upload and download speeds and other network parameters
- **Customers self update software, you can install apps with android version, such as Skype, wechat etc.**
- ONVIF camera test, support 2592*1520, Network PTZ controller (ONVIF)
- Built in Wi-Fi,display image from the wireless camera, **create WIFI hotspot**
- **4K video files and MKV/MP4 media files play**
- PoE DC48V power output, Max power 24W,12V /2A power output/5V 2A power output, as a power bank
- **Quick office**, quick office app (support excel, word, ppt format) doc. editable
- 8GB SD card including
- IP discovery, it can auto-scan the whole network segment IP, and auto-modify tester's IP address
- Enhanced Color bar generator, PAL/NTSC multi-system color bar video generator
- POE voltage measurement, PING test ,IP address scan, port flashing etc
- Audio in /out, support record and save the audio/LED lamp, calculators, music players, other application tools
- **7.4 V /5400mAh Lithium Ion Polymer Battery, after 5~6 hours charging , working time lasts 10 hours**

All above information only for reference, and reserve the right to change the parameters without prior notice.

VandalVeto®