

Metal standalone Keypad access control 800060



- ◆ Metal shell, attractive shape design, patent product
- ◆ With Anti-theft alarm output for external alarm device
- ◆ With standard Wiegand interface

Features

- Strong Zinc Alloy Electroplated anti-vandal case
- Full programming from the keypad
- 2000 uses, supports Card, PIN, Card + PIN
- Can be used as a stand alone keypad
- Backlight keys
- Wiegand 26 output for connection to a controller
- Adjustable Door Output time, Alarm time, Door Open time
- Very low power consumption (30mA)
- Fast operating speed, <20ms with 2000 users
- Lock output current short circuit protection
- Easy to install and program
- Built in light dependent resistor (LDR) for anti tamper
- Built in buzzer
- Red, Yellow and Green LEDS display the working status
- Two year warranty

Specifications

Operating Voltage	9-28V DC /AC
User Capacity	2000
Card Reading Distance	3-6 cm
Active Current	< 60mA
Idle Current	25±5 mA
Lock Output Load	Max 3A
Alarm Output Load	Max 20A
Operating Temperature	-45~60°C
Operating Humidity	10%- 90% RH
Environment	Conforms to IP54
Adjustable Door Relay time	0 -99 seconds
Adjustable Alarm Time	0- 3 minutes
Wiegand Interface	Wiegand 26 bit
Wiring Connections	Electric Lock, Exit Button,, External Alarm
Dimensions	L120 x W80x H25 mm

Noted: 800060 has luminous keypad, all digits blue illuminated