

AVM5547

WDR

WDR

Networking

5MP QSXGA



Motorized

Lens



H265

Eally Push Video EaZy



Recording

PoE

Mobile Surveillance

Line in / out

((L))

畎 External I/O



5MP H.265 IR Bullet IP Camera

O FEATURES

- Equipped with a motorized lens of f2.8 ~ 12mm
- Free P2P Cloud EaZy Networking
 - -- Cloud EaZy Networking available to connect this device to Internet automatically in three steps with our free mobile app, EagleEyes.
 - -- The Buddy feature to share the device access permission to other people.
 - -- Device login / out notifications reported.



- MicroSD card support (up to 128GB) for video storage
- External alarm I/O device connection

- **ONVIF** (**Onvif**) standard supported to simplify system integration
- POE (Power-over-Ethernet) support to eliminate the use of power cables and reduce installation costs
- Line in / out jacks available for audio transmission
- IR effective range up to 50 meters for night surveillance
- WDR to increase image recognizability in overexposure and dark areas
- Excellent outdoor ID design with cable management
- **Remote Surveillance**
 - -- Fully compatible with iOS and Android devices, and Internet Explorer on Windows operating system
 - -- Free PC program, CMS Lite, for 32CH devices monitoring on Windows operating system
 - -- Push Video available on your iOS and Android devices

VandalVeto®

• SPECIFICATIONS



LAN Port	YES
LAN Speed	10/100 Based-T Ethernet
Supported Protocols	DDNS, PPPoE, DHCP, NTP, SNTP, TCP/IP, ICMP, SMTP, FTP, HTTP, RTP, RTS RTCP,IPv4/IPv6, Bonjour, UPnP, DNS,UDP,IGMP, QoS, SNMP
ONVIF Compatible	YES (Profile S)
Number of Online Users	10
Security	(1) Multiple user access levels with password(2) IP address filtering(3) Digest authentication
Remote Access	(1) Internet Explorer on Windows operating system(2) CMS Lite, 32CH CMS software for Windows operating system(3) EagleEyes on iOS & Android mobile devices
Video	
Network Compression	H.265 / H.264 / MJPEG
Video Resolution	2592 x 1944 / 2048 x 1536 / 1920 x 1080 / 1280 x 720 / 640 x 480 / 320 x 240
Frame Rate	30/25 IPS
Multiple Video Streaming	4 (H.265 / H.264 / MJPEG)
General	
Image Sensor	1/2.9" SONY CMOS image sensor
Min Illumination	0.1 Lux / F1.4(Wide)~F2.8(Tele), 0 Lux (IR LED ON)
Shutter Speed	1/10,000 ~ 1/15 (Slow shutter)
S/N Ratio	More than 48dB (AGC off)
Lens	Motorized f2.8 ~ 12mm / F1.4 ~ F2.8 (Auto Focus)
Viewing Angle	Wide: 70.4° (Horizontal) / 65.6° (Vertical) / 87.4° (Diagonal) Tele: 25.9° (Horizontal) / 19.2° (Vertical) / 31.8° (Diagonal)
IR LED	6 units
IR Effective Distance**	Up to 50 meters
IR Shift	YES
Smart Light Control	YES
White Balance	ATW
AGC	Auto
IRIS Mode	AES
WDR	YES
POE	YES (IEEE 802.3af)
Defog	YES
External Alarm I/O	YES (1 input / 1 output)
Micro SD Card Slot	YES (up to 128GB)
RAM	20MB
IP Rating	IP66
Startup Temperature	0°C ~ 50°C
Operating Temperature	-40°C ~ 50°C
Operating Humidity	90% or less relative humidity
Power Source (±10%)	DC12V / 1A
Current Consumption (±10%)	225mA (IR LED OFF); 650mA (IR LED ON)
Power Consumption (±10%)	9.5W (PoE / PoN) ; 8W (DC Adapter)

VandalVeto[®]

.*The specifications are subject to change without notice. .







O SPECIFICATIONS (CONTINUED)

Line in	YES
Line out	YES
Others	
EaZy Networking	YES
Push Video	YES
Mobile Surveillance	iOS & Android mobile devices
Event Notification	Push Video / FTP / Email / SMS
Digital Pan / Tilt / Zoom	YES
Motion Detection	YES
RTC (real-time clock)	YES
Minimum Web Browsing Requirements	Intel core i3 or higher, or equivalent AMD2GB RAM
	AGP graphics card, Direct Draw, 32MB RAM
	Windows 10, Windows 8, Windows 7, Windows Vista & Windows XP, DirectX 9.0 or late
	 Internet Explorer 7.x or later (Windows Edge not supported)
Certification	CE

.*The specifications are subject to change without notice.

O DIMENSIONS





Dimensional tolerance: ± 5mm

