



## DC104

Surface mount contact, screw terminals - biased

### Easy Installation

---

The DC102-series are ideal for residential and commercial applications where terminal connections are preferred. The unit features positive clamping terminals with anti-rotation lugs and captured screws with combination heads. These features allow for easy, quick installations.

### Comprehensive Range

---

The range includes wide gap, SPDT and biased versions for higher security. This makes it one of the most popular contacts available in the industry today.

### Durability and dependability

---

These high performance magnetic contacts have been designed to facilitate installation and ensure durability and dependability. Most are conservatively rated at 10,000,000 cycles, guaranteeing a long life. Every reed connection is hand soldered and each magnetic contact is tested before they leave the factory.

### High quality components and materials

---

Reed legs are plated with rhodium or ruthenium, and hermetically sealed in dry nitrogen. This offers superior protection against sticking and provides a moisture free environment therefore preventing corrosion.



### Standard Features

---

- Ideal for residential and commercial
- Convenient surface mounting
- Versions with built-in resistors available

# DC104

Surface mount contact, screw terminals - biased

## Specifications

	Biased for high security
Operating gap	9 mm (min.); 31 mm (max.)
Connections	Screw
Contact type	CO
Dimensions (W x H x D)	63 x 12 x 19 mm
Colour	White

## Ordering Information

Part No.	Description
DC104	Surface mount contact, screw terminals - biased
DC1906T	Spacer for DC102, DC123, DC137, DC104
DC1906TM	
DC193	L Bracket for DC102, DC104, DC123, DC137

