

# Door Holder

## DH-60

**DH – 60** Without timer

**DH – 60T** Built in micro controller  
with door close delay function

### Specifications

- ◆ Fail safe (power to lock) electric lock suitable for fire exit
- ◆ Power saving function with fail safe design.  
No power consumption when both armature and electromagnetic door holder do not attached with each other
- ◆ **DH-60T** : Built in computer control board with  
door open delay function
- ◆ Built-in immediate power off push button  
Press the button to demagnetize the door holder  
to release the door immediately when both door holder and armature are attached
- ◆ Built-in demagnetizer design Instant demagnetization when power is off
- ◆ The armature is able to sway slightly in order to achieve maximum holding force when both armature and electromagnetic door holder are attached firmly in place
- ◆ 2 Mounting methods available -mounted on the floor or wall - depending on the environment
- ◆ Power Supply : 12vDC or 24vDC (adjustable)
- ◆ **HD-60** : 96mA@12vDC , 50mA@24vDC
- ◆ **HD-60T** : 113mA@12vDC , 70mA@24vDC
- ◆ Holding force : 55KG (120lbs)
- ◆ Operation temperature : 0° ~ 90°C , Humidity : 85% Rh Max.
- ◆ Dimension : Body 82.2(L)x50(W)x79(D)mm  
Armature 60(L)x60(W)x30(D)mm
- ◆ Weight : 700g
- ◆ Certification : CE

