# VandalVeto®





## VVSBTL5200 Series

**VVSBTL5200** Swing Barrier Turnstile for additional lane **VVSBTL5211** Swing Barrier Turnstile for additional lane

**VVSBTL5222** Swing Barrier Turnstile for additional (lane (w/ controller and fingerprint & RFID reader

VVSBTL5200 swing barrier turnstile for additional lane is an elegant cost-effective entrance control system designed for high-traffic volume. The VVSBTL5200 series should work together with VVSBTL5000 series to build multiple lanes

The **VVSBTL5200** is a swing barrier turnstile for additional Lane series designed for smooth and silent operation and draws very little power. It's made of stainless steel which makes SBTL5200 highly durable

VVSBTL5200 barriers are normally held in a locked position, thus denying access to the secured side. Upon SBTL5200's reader (RFID and/or fingerprint) positively recognizing a user's valid access card or fingerprint, its barriers swing automatically, thus allowing users passage to the secured side

**VVSBTL5200** provides both security and convenient space, all in a very durable and elegant compact design

### **Features**

#### Reliability

- SUS304 stainless steel case ensure long-lasting durability
- High quality electrical components Safety Features All smooth finish. No exposed screws
- Ergonomic design makes card and fingerprint authentication fast & simple for users

#### **Built-in Reader Integration**

- WSBTL5200 series already integrated with customers' preference for either card or fingerprint access control reader which greatly reduces installation time & expenses
- VVSBTL5200 series and associated access control readers have passed the factory test before shipment


#### Simplification


- Simplify structure and connection, easy to maintain
- Control board with LCD screen, easy to operate

## **Specifications**

Power requirements		AC 100 ~ 120V/200 ~ 240V, 50/60Hz
Working temperature		-28°C <b>~</b> 60°C
Working humidity		20%-95% (Non-condensing)
Working environment		Indoor
Speed of throughput	RFID	Maximum 30/ minute
	Fingerprint	Maximum 25/ minute
Lane width(mm)		650
Footprint(mm*mm)		1400*780
Dimensions(mm)		L=1400, W=180, H=1000
Dimension with packing(mm)		L=1500, W=260, H=1100
Net weight(kg)		72
Weight with packing(kg)		87
Cabinet material		SUS304 Stainless Steel
Lid material		Tempered Glass
Barrier material		Tempered Glass
Barrier movement		Swing
Emergency mode		Υ
Security level		Medium
MCBF		2 million

### **Dimensions (mm)**





### **VandalVeto®**

5 Korazin st., Givatayim 53583 Israel

Tel: 972-3-5713004 Fax: 972-3-5711450

egber@egber.com www.egber.com