

Biometric Tripod Turnstile



VVTS1000 Tripod Turnstile

VVTS1011 Tripod Turnstile with Controller and RFID Reader

VVTS1022 Tripod Turnstile with Controller and Fingerprint & RFID Reader

Tripod turnstiles are compact and cost-effective entrance solutions. Designing for smooth and silent operation, reducing power consumption, wear and tear. It is suitable for areas with a high traffic.


The **VVTS1000** series, our stainless steel compact version, offer high operating reliability in a small casework, ideal for sites where space is an issue. By receiving a signal from the access control system, or pushing button, it allows the entry of one person in a time. Entering into different directions are electronically controlled. Default mode is to lock the mechanism until a valid authorization signal is received. If you want to set one side free, you can adjust the mechanism. In case of emergency, the horizontal arm will drop to allow free passage

Features




Reliability

- Alloy steel tripod hub prevents mechanical wear
- Casework and tripod arms manufactured in SUS304 stainless steel
- Electromagnets for lock are used only when being activated. They are in standby mode when the device is idle.
- patented compact mechanism ensures the long life of the lubricating oil inside.
- High quality electrical components




Safety and User-Orientated Design

- Drop arm designed for emergency purpose
- No exposed screws, safer for the user.
- Smooth operation designed for mass transit application
- The pictogram on the device indicating access permission and direction of movement
- Special designed case shape, user-friendly for passenger to punch card or finger.
- Anti-tailgate



Easy Integration

- Flexible reader installation plate. Customers can easily integrate with third party reader
- Standard electrical interface for third party device.
- By using compact mechanism, the turnstile has more space inside for integration
- provides integration service, with board and peripherals installed, ensuring compliance of the system. When the turnstile is delivered, just plug it in and do the setting. Save the cost of installation




Specifications

Power Supply	AC 220V/110V, 50/60Hz
Operating Temperature	-28 °C- 60 °C
Operating Humidity	5%-85%
Working Environment	Indoor/Outdoor(shelter)
Rated Power	60W
Flow Rate	25- 48 passage/minute
Casework Material	SUS304
Pictogram Indication	Yes
Control System	Input controlled by dry contact
Emergency Button Input	Yes
Dimension	52×98×28(CM) + arm length 50CM
Package Dimension	60×108×38(CM)
Net Weight	34KG
Gross Weight with Package	40KG
Optional Function	Alternative material or shape, third-party access control integration, ticket system integration, passage counter

Model	VVTS1000	VVTS1011	VVTS1022
Access Control	N/A	VVC3-200	VWinBlo260
Reader	N/A	VVKR100E*2	VVFR12*2
Card Capacity	N/A	30,000	30,000
Fingerprint Capacity	N/A	N/A	3,000
Event Capacity	N/A	100,000	100,000

Dimensions (mm)



VandalVeto®

5Korazin st., 53583 Givatayim, Israel

Tel : 972-3-571304

Fax : 972-3-5711450

egber@egber.com

www.vandalveto.com