



1952N

AUDIO/VIDEO PORTER SWITCHBOARD. VIP



Tabletop audio-video porter switchboard with touch screen and alphanumeric keypad, for the simple and intuitive use of functions. Displays visitor images and the name of the user to call. Day/night mode and user/user intercom service. 12 VDC power supply with art. 43082 or direct from the ViP Ethernet network.



1952N

AUDIO/VIDEO PORTER SWITCHBOARD. VIP

ELECTRICAL CHARACTERISTICS

PoE power supply	Standard IEEE 802.3af, Comelit PoE (56VDC)
Maximum absorption (W)	11
Max/min absorption (mA)	50 ÷ 200

MAIN FUNCTIONS

Self Activation	Yes
-----------------	-----

GENERAL FEATURES

CE certifications	RoHS II - 2011/65/UE (EN 50581:2012), EMC 2014/30/UE (EN 61000-6-1:2007 , EN 61000-6-3:2007+A1:2011)
OSD display	Yes
Type of buttons	Mechanical

MAIN FEATURES

Height (mm)	110
Width (mm)	225
Depth (mm)	225
Product weight (g)	1100
Operating temperature (°C)	-5 ÷ 55
Operating humidity (RH max) (%)	25 ÷ 90
Maximum current absorption (mA)	200

SOFTWARE/FIRMWARE SPECIFICATIONS

No. of storable users (n°)	4000
----------------------------	------

GENERAL DATA

Type of finishing materials	ABS
Product color	Black
ViP	Yes
Display size (")	3.5



1952N

AUDIO/VIDEO PORTER SWITCHBOARD. VIP

GENERAL DATA

Display type	Graphic LCD
Touch screen	Yes
Number of push-buttons	28
Communication ports	RJ45 (Ethernet)
Loudspeaker volume	Yes
Microphone volume	Yes
Type of LAN network	Ethernet 10 Mbit/s
IP address assignment	Auto IP
Environmental class	III
Door opener	Yes

FUNCTIONS

Alarm function	Yes
Actuator control function	Yes
Intercom function	Yes
Key button function	Yes

MOUNTING/INSTALLATION

Desk base-mounted	Yes
-------------------	-----