

Specification:

Material:

- 1. Metal frame: SPCC.
- 2. Plastic Housing :PBT
- 3. RJ45 contact material & finished:
 - 3-1. Phosphor Bronze with Nickel plated.
 - 3-2. Contact area : 50u' Gold plated.

4. IDC Housing: PC

5. IDC Terminal material & finished:


- 5-1. Phosphor Bronze with Tin plated.
- 5-2. Krone & 110 tool compatible.
- 5-3. Suitable for 22-26 AWG stranded and solid wire.

Performance:

- a. The sticker color codes combine two wirings of T568A & T568B.
- b. Insertion Force: 900 gms for 8 contacts.
- c. Retention Strength: 7.7 kgs between Jack and Plug.
- d. Operation Temperature: -20. to 68. .

e. Durability:

- e-1. Jack : 750 cycles Plug-Jack mating and unmating test, Insertion cycles at 20 cycles/minute max. Contact resistance test per 100 cycles.
- e-2. IDC : Max. 200 punching times.
- f. The Cat.6 performance is in compliance with the ANSI/TIA/EIA 568 C.2 standard.

		Tolerance: X. ±0.5 .X ±0.3 .XX ±0.10		SCALE: FREE	CUSTOMER:	 VandalVeto®		 אגבר אלקטרוניקה 2000 בע"מ • 03-5711450 • פקס • 03-5713004 • סל' • 53583 • דו עמיתים • www.egber.com • egber@egber.com •		Approved by
		Angle: X' ±3' .X' ±1'		UNIT: mm					Item Number: 601126	
REV.	DESCRIPTION	DATE		REV.: 00	SHEET 1/1		DWG. No.:		TITLE: Cat 6 FTP patch panel, 24port,1U	