



## DC108

Surface - overhead - floor mount contact

### Overhead Door Magnetic Contact

The DC108 series overhead door magnetic contact is for use in the rigorous environments of commercial and industrial installations. The floor mount units are constructed with a low profile heavy cast aluminium housing. The reed switch assembly is fully encased in an exclusive polyurethane potting material to prevent damage due to moisture or humidity.

### Easy Installation

A wide operating gap distance of up to 7.5 cm makes installation easy and helps prevent false alarms caused by door movement or damaged and loose fitting doors.



### Standard Features

- Miniature, low-profile design
- Stainless steel armoured cable for added security, reliability
- Wide working gap for overhead doors
- Small size less likely to be damaged by forklifts
- Tamper loop provided

# DC108

Surface - overhead - floor mount contact

## Specifications

Operating gap	75 mm (max.)
Connections (armoured cable)	4 wires, 2 m
Contact type	NC
Dimensions (W x H x D)	
Magnet	89 x 38 x 38 mm
Contact	89 x 38 x 38 mm
Material	Aluminium

## Ordering Information

Part No.	Description
DC108	Surface - overhead - floor mount contact
DC108R4.7	Surface - overhead - floor mount contact with 4.7K resistor
DC140	Surface - overhead - floor mount contact - anti-corrosion
DC109	Surface - overhead - floor mount contact - extra heavy duty

