

Outdoor - Infrared Beam Detector

201028-201034 Series

Features:

- 4 frequencies for option to offer an effective solution to mutual interference among each group of barriers .
- Bi-directional mutual-transmission operation way to avoid sunshine interference .
- AGC control circuit to confirm its normal operation in very severe environments such as wind, frost, rain, snow , fog etc.
- Hint of aiming status, more convenient and quick installation .
- Multi layers technical process on anti-thundering, water-proof and static-immunity .
- Qualified aluminum alloy housing, special and elegance appearance design .
- 360° for horizontal rotation, convenient for installation and usage .
- Military and industrial grade transmission, receiver works with non-spherical lens to get more stable operation and longer distance .
- Multi height and operation distances for option .
- Intelligent pet-immunity technology .
- It is fit for installation in terrace, windows, alley, warehouse, villa, military area and governmental offices etc.



201028	2 Beams	37cm Length
201030	4 Beams	74cm
201031	6 Beams	115cm
201032	8 Beams	140cm
201035	10 Beams	165cm
201034	12 Beams	200cm

Brand Name	VandalVeto®
IP	IP 65
Usage	Window
Distance	25m
Voltage	DC 13.8-24V AC 11-18V . S.B 120mA . ALARM 280 mA
Alarm Output	CN CO Contact capacitor AC, DC 30V/0.5mA
Operation Temperature	-25°C-+60°C
Tamper output	Normal close (NC) touching capability AV/DC 24V/0.5mA