



NOTES:

ELECTRICAL:

1. VOLTAGE RATING:125 VAC RMS
2. CURRENT RATING:1.5AMP
3. CONTACT RESISTANCE:100MILLIOHMS MAX
4. INSULATION RESISTANCE:1000 MEGOHMS MIN @500 VDC
5. DIELECTRIC STRENGTH:750 VAC RMS 60Hz, 1MIN

ENVIRONMENTAL:

1. STORAGE:-40° TO +85°
2. OPERATION:0° TO 70°

MECHANICAL:

1. HOUSING MATERIAL:PBT UL94V-0;
2. PANEL FRAME:CARBON STEEL, POWDER, COATING IN BLACK COLOR, Specl. 6mm;
3. PCB MATERIAL:FR-4 T=1.6mm;
4. IDC MATERIAL:PC , CONTACT:PHOSPHOR BRONZE; WITH NICKEL PATING;
5. RJ45 JACK LIFE:750 TIMES MIN;
6. IDC LIFE:200 TIMES MIN;
7. WIRE:AWG 22-26;

					<p>אגבר אלקטרוניקה 2000 בע"מ יבוא ושיווק מערכות אבטחה ותקשורת Email: egber@egber.com 03-5711450 :פקס 03-5713004 :טל 53583 גבעתיים 5, רח' כורזין www.egber.com VandalVeto®</p>				
SYM		Number	Bill No. of Alteration	Signature	Date	Material	Item No.	601129	
Angles Projection		Size	Scale	Unit	Part Name	24Ports Cat6A STP Patch Panel			
Drawn	Ding jian bo	2015.1.6	Tolerance			A4	X:1	mm	ERP
Checked	Ge pei jun	2015.1.6	0.00-20.00 ±0.10	20.00-50.00 ±0.15		Sheet	1 OF 1	Version: A/0	Part No.
Approved	Wang wei jun	2015.1.6	50.00-100.00 ±0.20	100.00- Angle ±0.25 ±30°			10100327		