



6741W

MINI HANDSFREE WIFI MONITOR, S2



SB2

"Wall-mounted hands-free monitor with full-duplex audio and 4.3" / 16:9 colour screen. It is equipped with a Wi-Fi port to allow calls forwarding to mobile devices. Allows brightness control, plus adjustment of the ringtone volume, which can be customised by choosing one of several different melodies. Equipped as standard with 8 sensitive touch back-lit controls for audio activation, door-opening, self-ignition, switchboard call, privacy service and LED signalling for the door status. Manages floor door calls as standard. Complete with 2 x 8-position dip-switch for user code programming and button programming. The wall-mounting backplate and riser distribution terminal art. 1214/2C are included. The monitor can only be used in 2-wire system Simplebus 2. Dimensions: 4.53"x6.3"x0.87"."

AWARDS





6741W

MINI HANDSFREE WIFI MONITOR, S2

GENERAL DATA

Product height (inch) (mm)	160
Product width (inch) (mm)	115
Product depth (inch) (mm)	22
Product weight (oz) (g)	400.00
Product color	White RAL9003
Material	ABS
Wall mounting	Yes
Desk base-mounted	Yes, with a dedicated accessory

COMPATIBLE SYSTEMS

Audio/video Simplebus 2 with power supply art. 4888C	Yes
Audio/video Simplebus 2 with power supply art. 1210	Yes
Simplebus 2 audio/video kit with power supply art. 1209	Yes

DISPLAY FEATURES

Size (inches) (")	4.30
Aspect Ratio	16:9
Resolution (pixels)	480x272
OSD menu	Yes

AUDIO FEATURES

Type	Hands-free
Microphone	6mm (Ø), Omnidirectional
Loudspeaker	36mm (Ø), 40 Ohm, 1W

ELECTRICAL CHARACTERISTICS

The technical specifications are subject to change without prior notice.



6741W

MINI HANDSFREE WIFI MONITOR, S2

Type of power supply	Power supply from video door entry bus
Supply voltage	22÷34 VDC (Bus)
Stand-by absorption (W)	0.10
Stand-by absorption in kit mode (W)	1.90
Maximum absorption (W)	8.10

HARDWARE FEATURES

Type of buttons	Capacitive
Service buttons	Answer, Silent (Privacy), Menu, Messages, Door open
No. of programmable buttons for additional functions	4
Terminals	L L CFP1 CFP2
Removable terminals	Yes

SETTINGS

Loudspeaker volume	Yes
Ringtone volume	Yes
Screen brightness	Yes

NETWORK AND COMMUNICATION PROTOCOLS

Type of Wi-Fi connection	IEEE 802.11 b/g/n, 2.4 Ghz, 13 channels
Encryption and authentication method supported	OPEN WPA-PSK networks, TKIP WPA2-PSK, AES WEP 64 bits (5-digit ASCII or 10 hexadecimal codes), WEP 128 bits (13-digit ASCII or 26 hexadecimal codes)
IP address assignment	DHCP
IoT connection to Comelit Cloud	Yes
Firmware update via Comelit Cloud	Yes

ENVIRONMENTAL AND COMPLIANCE FEATURES

IP protection degree	IP30
----------------------	------



6741W

MINI HANDSFREE WIFI MONITOR, S2

ENVIRONMENTAL AND COMPLIANCE FEATURES

Operating temperature (°K) (°C)	5 ÷ 40
Operating humidity (RH max - %) (%)	25 ÷ 75
Environmental class	I
Compliance and Certifications	RoHS II - 2011/65/UE (EN 50581:2012), RED 2014/53/UE (EN 60950-1:2006+A11:2009+A1:2010+A12:2011, +A2:2013, EN 62311:2008, EN 61000-6-1:2007, EN 61000-6-3:2007 + A1:2011, ETSI EN 301 489-1 V2.2.0, ETSI EN 301 489-17 V3.2.0, ETSI EN 300 328 V2.1.1)

MAIN FUNCTIONS

Compatibility with Comelit app	Yes
Door opener	Yes
Self Activation	Yes
Intercom calls	Yes
Actuator control	Yes
CPS call	Yes
Outside door call input	Yes
Silent mode (Privacy)	Yes
Video memory	Yes
Door opening on call (Doctor)	Yes
Automatic answer (handsfree)	Yes
Door open signaling	Yes
Multiple address	Yes
Customizable ringtone	Yes
Date/time display	Yes
Sending alarm calls	Yes



6741W

MINI HANDSFREE WIFI MONITOR, S2

ACCESSORIES



6711WV ADAPTER PLATE FOR MINI HANDSFREE

Adapter plate to finish the installation of the Mini Handsfree monitor in case of replacement of flush-mounted or wall-mounted Planux, Smart and Icona monitors. White color. Dimensions: 170x220x3 mm.



6732A DESK BASE FOR HANDS-FREE MINI MONITOR. S2

Desk base installation accessory for hands-free Mini monitor in Simplebus 2 system.



6720 Access. cables external passage for MINI HF. S2

Wall support bracket for handsfree Mini monitor allowing thru-routing of external cables.