IP CABLING TRANSMISSION - POE Repeater

ITEM NO.: 800916



800916 is a POE repeater to extend power and data an additional 100meters. Multiple units are allowed for longer distance, eliminating the need for additional switches, hubs and expensive fiber installations. It compliant with standard POE IEEE802.3af.

800916 POE Repeater

- Extend of both power and data beyond 100 meters.
- Allow to use multiple repeaters for longer range.
- No external power required.
- Compatible IEEE 802.3af POE standard.
- Auto-sensing for detecting PoE or non-PoE devices.
- Support 10/100/1000 BASE-T transmission rate.
- Built in LED status indication.
- Plug and play for easy installation.


Installation View:


800916 itself provide data and power 120 meters, the power will drop as below by multiple POE repeaters and long cable length application:

Max Device Power	1 st 800916 Max.	2 nd 800916 Max.
Range with PoE switch	8.58W at 240M	4.21W at 360M



Panel View:





Linking Cable:

Use CAT.5e UTP/STP or CAT.6 UTP cable

LED Indication:

LED (Green)	ON	PSE send power
	OFF	PSE non-power
RJ45 (Yellow)	ON	1000 Mbps link
	OFF	1000 Mbps unlink
	FLASH	Activity
RJ45 (Green)	ON	10/100 Mbps link
	OFF	10/100 Mbps unlink
	FLASH	Activity

Specification:

Specification:		
ITEM NO.	800916	
Power & Data Input/Output	RJ45	
Data Link	Pin 1/2, 3/6, 4/5, 7/8	
Power Link	Pin 1/2 (+) , 3/6 (-) End-Span	
Transmission Range	2 pieces repeater up to 360 Meters	
LED Indication	Power: Green, Data link: Yellow/Green	
POE	IEEE 802.3af Standard, 48V、12.95W	
Power Consumption	Non-load 1.1W (23mA), 1.44W (30mA) @ 10Mbps, 1.92W (40mA) @ 100/1000Mbps	
Temperature	Operation: 0 to 55°C, Storage: -20 TO 85°C, Humidity: up to 95%	
Dimensions mm	67×110×27 mm	
Weight g	180g	

Rohs ((FC C

Rev.C

