



KAE5064

EXTRA-MINI 5-WIRE FOUR-FAMILY AUDIO KIT



The kit includes: four Mini series door-entry phones art. 2702W, a transformer art. 1200, an Extra series external unit designed for 2/4 call buttons art. ET5100, 4 single buttons for Extra entrance panel art. ET9211. The kit can be expanded with another door-entry phone for each user. The external unit can be surface-mounted or flush-mounted using the corresponding accessories supplied with the kit.

AWARDS





KAE5064

EXTRA-MINI 5-WIRE FOUR-FAMILY AUDIO KIT

KIT PRODUCTS



ET5100 EXTRA 4+N ENTRANCE PANEL PREPARED FOR 2/4 BUTTONS

Extra series audio entrance panel with stainless steel cover and nameplate backlighting. To be completed with single button art. 9211 (pack of 4 units) to offer 4 call buttons, or with double-height button art. 9210 (pack of 2 units) to offer 2 call buttons. The entrance panel can be surface-mounted or flush-mounted using the relevant accessories supplied. Traditional 4 + N wiring system. Dimensions (W x H x D): 95x165x6.5 mm (flush) - 25 mm (surface).

FEATURES

Type	Monoblock
------	-----------

MOUNTING/INSTALLATION

Flush-mounted	Yes
Wall-mounted	Yes



KAE5064

EXTRA-MINI 5-WIRE FOUR-FAMILY AUDIO KIT



2702W 2-BUTTON MINI DOOR-ENTRY PHONE, TRADITIONAL

MINI series door-entry phone for traditional system with electronic call and key button. Call volume and privacy adjustment by means of 3-position selector. Privacy activation is indicated by a red light.
Dimensions: 105x191x28 mm

GENERAL DATA

Height (mm)	189.99
Width (mm)	103.12
Depth (mm)	29.97

SETTINGS

Loudspeaker volume control	Yes
Microphone volume control	Yes
Ringtone volume control	Yes

MAIN FEATURES

Audio system	Yes
Wall-mounted	Yes
Desk base-mounted	Si
Colour	White
Total buttons (n°)	2

FUNCTIONS

Actuator control function	Yes
Privacy function	Yes
Electronic bell	Yes
Key button function	Yes

COMPATIBILITY

Traditional system	Yes
--------------------	-----



KAE5064

EXTRA-MINI 5-WIRE FOUR-FAMILY AUDIO KIT

TECHNICAL CHARACTERISTICS

Supply voltage	15÷16VDC
Absorption during call (mA)	0.42
Absorption during communication (mA)	0.35
Microphone	4mm, omnidirectional
Operating temperature (°C)	-5 ÷ 40
Weight (g)	258.55
Clamps	S 2 3 4 P1 P2



KAE5064

EXTRA-MINI 5-WIRE FOUR-FAMILY AUDIO KIT



1200 TRANSFORMER 10VA 0-230V/0-12V

Transformer with 230V primary winding, 12V AC / 900 mA secondary winding for continuous use. Dimensions: 53x95x65 mm (3 DIN modules).

MAIN FEATURES

Supply voltage	230
Input connector	Terminal block
Applicable to DIN rail	Yes
Number of DIN modules (n°)	3
Max. current delivered (A)	0.9

GENERAL DATA

Height (mm)	95
Width (mm)	53
Depth (mm)	65
Type of finish	Plastic
Operating temperature (°C)	-5 ÷ 40

COMPATIBILITY

Simplebus 2 audio/video system	Yes
Building Kit audio/video system	Yes
Simplebus 2 audio system	Yes
Simplebus 1 audio system	Yes
Vip system	Yes
Kit audio/video system	Yes
Traditional system	Yes
Simplified system	Yes

ELECTRICAL SPECIFICATIONS

Maximum power delivered (W)	15
-----------------------------	----



KAE5064

EXTRA-MINI 5-WIRE FOUR-FAMILY AUDIO KIT

ACCESSORIES



ET9150 Flush-mounted box for Extra entrance panel kit

Flush-mounted box for Extra series external unit art. ET5001 - ET5002 - ET0001. Dimensions: 134.5 x 93.5 x 25 mm



ET9160 Wall bracket for Extra entrance panel kit

Wall housing for Extra series external unit art. ET5001 - ET5002 - ET0001. Dimensions: 94 x 134 x 19 mm



1229 EXTENSION SOUNDER

Additional bell for call repetition can be controlled directly from terminals S- and S+ of the brackets and/or from the telephones. Surfaced mounted or on civil series 503 box. Dimensions: 110X75X29 mm.