



KCA2061

Ciao-Mini one-family audio kit. HS.S2



The kit includes: 1 art. CA2100P - wall-mounted CIAO entrance panel designed for 1/2/4 buttons, 1 art. 2738W - 2-button MINI door-entry phone, 1 art. CA9210 - 2 double-height buttons for CIAO entrance panel, 1 art. CA9211 - 4 single buttons for CIAO entrance panel, 1 art. CA9213 - 1 large button for CIAO entrance panel, 1 art. 1209 - video kit power supply unit. Wiring for 2-wire setup.



KCA2061

Ciao-Mini one-family audio kit. HS.S2

ACCESSORIES



CA9212 4 DOUBLE BUTTONS FOR CIAO ENTRANCE PANEL

Double buttons for use with the Ciao series entrance panel.



CA9211 4 SINGLE BUTTONS FOR CIAO ENTRANCE PANEL

Single buttons for use with the Ciao series entrance panel.



CA9210 2 DOUBLE-HEIGHT BUTTONS FOR CIAO ENTRANCE PANEL

Double-height buttons for use with the Ciao series entrance panel.



CA9213 1 LARGE BUTTON FOR CIAO ENTRANCE PANEL

Large button for use with the Ciao series entrance panel.



CA2200P CIAO WALL-MOUNTED MODULE FOR 2/4/8/16 BUTTONS. S2

Ciao series button module with die-cast aluminium front cover and nameplates with white LED backlighting. To be finished with 2/4/8/16 call buttons (art. CA9210, CA9211, CA9212 and 2 x CA9212 respectively), available to purchase separately. Supplied with a surface-mount installation support. Can be used alongside up to 4 button modules (both horizontally and vertically).



KCA2061

Ciao-Mini one-family audio kit. HS.S2

ACCESSORIES



CA2100P CIAO WALL-MOUNT ENTRANCE PANEL FOR 1/2/4/8 BUT. S2

Ciao series modular entrance panel with die-cast aluminium front cover and nameplates with white LED backlighting. To be finished with 1/2/4/8 call buttons (art. CA9213, CA9210 CA9211 and CA9212 respectively), available to purchase separately. Featuring a smart button programming mode. Supplied with a surface-mount installation support. Entrance panel art. CA2100P can be used alongside up to 4 button modules art. CA2200P (both horizontally and vertically) to reach a maximum of up to 72 call buttons.



2738W 2-BUTTON MINI DOOR-ENTRY PHONE, S2

MINI series door-entry phone for Simplebus 2 system with electronic call, key button and additional button for extra services (switchboard call, actuator and generic uses). Call volume and privacy adjustment by means of 3-position selector. Privacy activation is indicated by a red light. Allows floor door call management. Complete with 8-position dip-switch for selection of the desired user code. Door-entry phone for use in mixed audio/video Simplebus 2 systems. Fitted with terminal art. 1214/2C. Dimensions: 105x191x28 mm



1209 2-WIRE VIDEO KIT POWER SUPPLY UNIT

33 VDC power supply unit with overload and short circuit protection devices. It has two separate continuous outputs: one to power the external unit and electric lock, and the other to power the monitor. Input voltage 110-240 VAC. Dimensions: 106x62x89mm (6 DIN modules).