

## VMT900 A CCTV Multifunction Tester with 2.8" monitor

1. 2.8 "TFT-LCD Monitor
2. Multifunctional Menu: English; France and Spanish
3. Automatic NTSC/PAL display,  
NTSC/PAL standard color bar image generator
4. Analysis and test of Video Signal intensity



	<b>VMT900-A</b>
Signal mode	NTSC/PAL (Auto adapt)
Display	2.8 inch digital TFT-LCD ,960 x 240 resolution
LCD adjustment	Brightness, Contrast, Saturation adjustable
Video IN/OUT	1 channel BNC Input & 1 channel Output
Video Output Mode	1.0 Vp-p
Communication	RS232, RS422 simplex and RS485
PTZ Protocol	Compatible with more than 20 protocols such as PELCO-D/P, Samsung, Panasonic, Lilin, Yaan, etc.
Baud Rate	150,300,600,1200,2400,4800,9600,19200bps
Color bar generation	Output channel color bar video signal for testing monitor or video cable
UTP cable test	Test UTP cable connection status and display in the screen. Read the number of the test box.
Data Monitor	Captures and analyzes the command data from controlling device
Power Adapter	DC5V, 2A
Battery	Built-in 3.7V Lithium polymer battery ,3000mAh
Rechargeable	After charging 3-4 hour, working time lasts 11 hours
Low Consumption	Energy saving technology
Working Temperature	-30°C---+70°C
Working Humidity	30%-90%
Dimension/Weight	176mmx94mmx36mm/340g

**VandalVeto®**