



**1406**

**SB2 APARTMENT BLOCK CALL FORWARDING MODULE**



Multi-user call forwarding module for Simplebus 2 system, for video entry phone call transmission on smartphones/tablets which have the SimpleApp installed on them; external unit self activation; is also possible, in addition to the sending of lock-release commands. The module needs an internet connection with suitable bandwidth to work properly. The module supports up to 50 apartments and 15 enabled users for each apartment. For systems with more than 50 apartments, several modules can be installed. Call receipt on SimpleApp is only enabled if a Comelit internal unit is installed inside the apartment. The module has 1 Ethernet port for internet connection; it has a 12-56 VDC power supply input and L-L terminals for interfacing with the Simplebus 2 system. Dimensions 70x90x62 mm (4 DIN modules).



**1406**

**SB2 APARTMENT BLOCK CALL FORWARDING MODULE**

**MAIN FEATURES**

Height (mm)	59
Width (mm)	70
Depth (mm)	90
Operating temperature (°C)	5 ÷ 50
Operating humidity (RH max) (%)	25 ÷ 95
IP protection rating	IP20
DIN rail mounted	Yes
DIN modules (no.) (n°)	4

**SOFTWARE/FIRMWARE SPECIFICATIONS**

IP assignment	
---------------	--

**CONNECTIVITY**

Ethernet ports (n°)	1
---------------------	---

**ELECTRICAL SPECIFICATIONS**

Supply voltage	12÷56VDC
Max/min absorption (mA)	80 ÷ 250