

NOTES:

ELECTRICAL:

1. VOLTAGE RATING: 125 VAC RMS
2. CURRENT RATING: 1.5AMP
3. CONTACT RESISTANCE: 100MILLIOHMS MAX
4. INSULATION RESISTANCE: 1000 MEGOHMS MIN @500 VDC
5. DIELECTRIC STRENGTH: 750 VAC RMS 60Hz, 1MIN



ENVIRONMENTAL:

1. STORAGE: -40° TO +85°
2. OPERATION: 0° TO 70°

MECHANICAL:

1. THE SHELL MATERIAL: NICKEL PLATED BRASS, T=0.2mm
2. HOUSING MATERIAL: PC
3. INSERT MATERIAL: ABS
4. PCB MATERIAL: FR-4 T=1.6mm
5. CONTACT MATERIAL: PHOSPHOR BRONZE
STAMP PIN Ø0.40mm
6. RJ45 JACK LIFE: 750 TIMES MIN

SYM	Number	Bill No. of Alteration	Signature	Date
Drawn			Tolerance	
Checked			0.00-20.00	±0.10
			20.00-50.00	±0.15
			50.00-100.00	±0.20
Approved			100.00-	±0.25
			Angle	±30'

 VandalVeto®		אגבר אלקטרוניקה 2000 בע"מ • 03-5711450 : פקס • 03-5713004 : טל • 53583 : גבעתיים • • www.egber.com • egber@egber.com •			
		Material	Item No.		601051
Angles Projection	Size	Scale	Unit	Part Name	STP CAT.6A Keystone Jack
	A4	X:1	mm	ERP	
Sheet	1 OF 1	Version: A/0		Part No.	