# DGM8937SVAT



8MP



H.265



Starlight



PoE



WDR

•



MIC built-in



Human / Vehicle Detection

33x zoom

33X Optical 700m

500

PTZ


MicroSD Card Recording

#### Al-based 8MP H.265 33X Speed Dome IP Camera

#### O FEATURES

- Starlight visibility to offer clear & color images even at night
- Zoom lens of f4.5 ~ f148.5mm with 33X optical zoom, suitable for various monitoring environments
- Al-based human / vehicle detection supported to avoid false detection alarms
- PTZ control with Auto Tracking for seamless monitoring:
- MicroSD card support (up to 256GB) for video storage
- **ONVIF** standard supported to simplify system integration
- POE (Power-over-Ethernet) support to eliminate the use of power cables and reduce installation costs
- Microphone built-in for audio recording and line out support for audio broadcasting
- IR effective range up to 120 meters for night surveillance
- WDR to increase image recognizability in overexposure and dark areas
- **Remote Surveillance** Compatible with Internet Explorer 6 and above, Microsoft Edge & Google Chrome

#### O DIMENSIONS



### **O SPECIFICATIONS**

Image Sensor  Max. Resolution  Lens  Viewing Angle  Min Illumination  Shutter Speed  IR LED  IR Effective Distance  Day / Night  WDR Mode  RTC (real-time clock)		1/2.8" SONY CMOS  3840 x 2160  f4.5-148.5mm / F1.6 - F3.5  Tele 2.3° ~ Wide 60.5° (Diagonal)  0.001 Lux (IR LED off), 0 Lux (IR LED on)  AUTO, 1/25s ~ 1/100000s  8 units  Up to 120 meters
Viewing Angle Min Illumination Shutter Speed IR LED IR Effective Distance Day / Night WDR Mode		f4.5-148.5mm / F1.6 - F3.5  Tele 2.3° ~ Wide 60.5° (Diagonal)  0.001 Lux (IR LED off), 0 Lux (IR LED on)  AUTO, 1/25s ~ 1/100000s  8 units
Viewing Angle Min Illumination Shutter Speed IR LED IR Effective Distance Day / Night WDR Mode		Tele 2.3° ~ Wide 60.5° (Diagonal)  0.001 Lux (IR LED off), 0 Lux (IR LED on)  AUTO, 1/25s ~ 1/100000s  8 units
Min Illumination Shutter Speed IR LED IR Effective Distance Day / Night WDR Mode		0.001 Lux (IR LED off), 0 Lux (IR LED on)  AUTO, 1/25s ~ 1/100000s  8 units
Shutter Speed IR LED IR Effective Distance Day / Night WDR Mode		AUTO, 1/25s ~ 1/100000s 8 units
IR LED IR Effective Distance Day / Night WDR Mode		8 units
IR Effective Distance Day / Night WDR Mode		-
Day / Night WDR Mode		Up to 120 meters
WDR Mode		
		YES
RTC (real-time clock)		YES (120dB)
RTC (real-time clock)		YES
MicroSD Card Slot		YES (up to 256GB)
Video		
Compression		H265 / H.264
Video Resolution	Main Stream	8MP (3840x2160) / 6MP (3072x2048) / 5MP (2592x1944) / 4MP (2560x1440) / 3MP (2304x1296) / 2MP (1080P) / 720P
	Sub Stream	2MP (1080P) / 720P / 720x480 / VGA / 640x360 / 480x360 / CIF
Frame Rate		4K (8MP) @ 20FPS
Video Profile		High profile / Main profile / Base profile
Multiple Video Streaming		3 streams
Bitrate Control		512Kbps - 12Mbps, VBR/CBR
Image Enhancement		WDR / BLC / HLC / 2D DNR / 3D DNR / AWB / MWB / AGC
Day / Night Switch		Auto / Color / (B/W) / Timing
Forced Anti-flicker		YES
Defog		YES
White Balance		Auto / Manual
Image Orientation		Rotate / Mirror
Privacy Mask		YES
Text Overlay		YES
OSD Title		Location / font size / text configurable; text input (English & Chinese characters) and imagupload (BMP) supported
Audio		
Microphone built-in		YES
Line out		YES
Encoding		G.711-u / G.711-a
Audio Adjustment		YES
Alarm & Event		
Detection Mode		Motion / Human / Vehicle Detection with Auto Tracking
Detection Schedule		YES
Motion Detection Area		1x1, 2x2, 3x2, 3x3, 4x4, 8x8, 16x16, 22x18
Detection Alert		Audio alert with customized mp3 audio file(s)



## • SPECIFICATIONS (CONTINUED)

Storage	
On-Board Storage	Built-in memory card slot, supports microSD / SDHC / SDXC card up to 256GB
Overwrite	YES
Maximum Recoding Time / per File	1, 2, 3, 5, 10, 20 & 30 minutes configurable
Recording Schedule	YES
Network	
LAN Port	RJ45 connector x 1 / 4KV lightning-proof
LAN Speed	100Mbps Based-T Ethernet
Supported Protocols	HTTP / RTSP / FTP / SMTP / DHCP / NTP / NFS / RTMP
ONVIF Compatible	Onvif 17.06 compatible
Number of Online Users	6
Remote Access	Internet Explorer 6 and above (recommended), Microsoft Edge & Google Chrome
PTZ Mechanism	
Pan Range	360° continuous rotation
Pan Speed	0.5° ~ 60°
Tilt Range	-15° ~ 90°/s
Zoom Ratio	33X Optical Zoom
Proportional Zoom	YES
Auto Tracking	YES
Preset Points	Up to 255 preset points
Tour	8 sets
General	
Web Interface Language	English, Traditional Chinese, Simplified Chinese, Russian, German, Italian, Turkish, Koro
Operating Temperature	-30℃ ~ 60℃
Operating Humidity	10% ~ 90%RH
POE	IEEE 802.3af
Power Source (±10%)	PoE / DC12V
Power Consumption (±10%)	< 20 W
Net Weight (kg)	2.5
Casing	IP66
Minimum Web Browsing Requirements	<ul> <li>Intel core i3 or higher, or equivalent AMD</li> <li>2GB RAM</li> <li>AGP graphics card, Direct Draw, 32MB RAM</li> <li>Windows 10, Windows 8, Windows 7, DirectX 9.0 or later</li> <li>Internet Explorer 6 and above (recommended), Microsoft Edge &amp; Google Chrome</li> </ul>

.\*The specifications are subject to change without notice.