

## 36-port Gigabit Managed Ethernet Fiber Switch # 700652

**VandalVeto**



### OVERVIEW

The 700652 is a gigabit managed Ethernet fiber switch independently developed by Vandalveto. It has 8\*10/100/1000Base-T RJ45 ports and 28\*100/1000Base-X SFP ports. Each port can support wire-speed forwarding.

The 700652 has L2+ full network management function, support IPV4/IPV6 management, static route full line rate forwarding, complete security protection mechanism, ACL/QoS policy and rich VLAN functions, and is easy to manage and maintain. Supports multiple network redundancy protocols STP/RSTP/MSTP (<50ms) and (ITU-T G.8032) ERPS(<20ms) to improve link backup and network reliability. When one-way network fails, communication can be quickly restored to ensure important Uninterrupted communication for applications. According to the actual application requirements, you can configure multiple application services such as port traffic control, VLAN division, and SNMP through the Web network management mode. It satisfies high-density network application environment and is suitable for medium, large-scale scenes such as hotel, campus, park, shopping mall, scenic spot, hospital, bank to form an economical, efficient and reliable communication network.

## FEATURE

### ■ Gigabit multi fiber port access

- ◇ All series supports “Gigabit Ethernet port and gigabit SFP fiber slot port” combination, which enables users to flexibly build networking to meet the needs of various scenarios.
- ◇ Support non-blocking wire-speed forwarding.
- ◇ Support full-duplex based on IEEE802.3x and half-duplex based on backpressure.

### ■ Strong business processing capability

- ◇ IEEE802.1Q VLAN, flexible VLAN division, Voice VLAN and QinQ configuration.
- ◇ QoS, Priority mode based on 802.1P, Port & DSCP, queue scheduling algorithm including Equ, SP, WRR & SP+WRR.
- ◇ ALC, filter data packet through configuring matching rules, processing operation & time permission, and provide flexible and safe access control.
- ◇ IGMP V1/V2 and IGMP Snooping.
- ◇ ERPS/STP/RSTP/MSTP.
- ◇ Static and dynamic aggregation.

### ■ Security

- ◇ 802.1X authentication.
- ◇ Port isolation, Storm control.
- ◇ IP-MAC-VLAN-Port binding.

### ■ Stable and reliable

- ◇ CCC, CE, FCC, RoHS.
- ◇ Low power consumption, galvanized steel casing.
- ◇ Self-developed power supply, high redundancy design, providing a long term and stable power output.
- ◇ The user-friendly panel, it can show the device status through the LED indicator of PWR, SYS, Link/A.

## ■ Easy operation and maintenance management

- ◇ Web management, CLI command line (Console, Telnet), SNMP (V1/V2/V3).
- ◇ HTTPS, SSLV3, and SSHV1/V2.
- ◇ RMON, system log, LLDP, and port traffic statistics.
- ◇ CPU monitoring, memory monitoring, Ping test, and cable diagnose.

## TECHNICAL SPECIFICATION

Model	700652	700654
<b>Interface Characteristics</b>		
Fixed Port	8*10/100/1000Base-T RJ45 ports (Data) 28*100/1000Base-X SFP ports (Data) 1*Console RS232 port (115200,N,8,1)	8*10/100/1000Base-T RJ45 ports (Data) 24*100/1000Base-X SFP ports (Data) 4*1/10G SFP+ ports (Data) 1*Console RS232 port (115200,N,8,1)
Ethernet Port	Port 1-8 support 10/100/1000Base-T,auto-sensing,Full/half duplex MDI/MDI-X self-adaption	
Twisted Pair Transmission	10BASE-T: Cat3,4,5 UTP(≤100 meter) 100BASE-TX: Cat5 or later UTP(≤100 meter) 1000BASE-T: Cat5e or later UTP(≤100 meter)	
SFP Slot Port	1/10G SFP+ optical fiber interface, default not matching optical modules (optional order single-mode / multi-mode, single fiber / dual fiber optical module. LC)	
Optical Cable/ Distance	Multi mode: 850nm / 0~ 500m single mode: 1310nm / 0~ 40km, 1550nm / 0~ 120km	Multi-mode: 850nm / 0~ 500m(1.25G), 0-300m(10G), single mode: 1310nm / 0~ 40km,

		1550nm / 0~ 120km
<b>Chip Parameter</b>		
Network Management Type	L2+	
Network Protocol	IEEE802.3 10BASE-T IEEE802.3i 10Base-T IEEE802.3u 100Base-TX IEEE802.3ab 1000Base-T IEEE802.3z 1000Base-X IEEE802.3x	IEEE802.3 10BASE-T IEEE802.3i 10Base-T IEEE802.3u 100Base-TX IEEE802.3ab 1000Base-T IEEE802.3z 1000Base-X IEEE802.3ae 10GBase-SR/LR IEEE802.3x
Forwarding Mode	Store and Forward(Full Wire Speed)	
Switching Capacity	598Gbps	
Forwarding Rate@64byte	53.57Mpps	107.14Mpps
MAC	32K	
Buffer Memory	32M	
Jumbo Frame	9.6K	
LED Indicator	Power: PWR (yellow), System: SYS(yellow), Network: Link (yellow), Fiber port: L/A (green)	
Reset Switch	yes, support one key to restore factory settings	
Power Supply		
Total PWR / Input Voltage	60W/AC100-240V)	
Power Consumption	Standby<20W, Full Load<45W	
Power Supply	Built-in power supply, AC 100~240V 50-60Hz 1.0A	
<b>Physical Parameter</b>		
Operation TEMP /	-20~+55°C, 5%~90% RH Non condensing	

Humidity	
Storage TEMP / Humidity	-40~+80°C, 5%~95% RH Non condensing
Dimension (L*W*H)	440*290*44.5mm
Net /Gross Weight	<3.5kg / <4.3kg
Installation	Desktop, 19 inch 1U cabinet installation
<b>Certification &amp; Warranty</b>	
Lightning protection / protection level	Lightning protection: 4KV 8/20us, Protection level: IP30
Certification	CCC, CE mark, commercial, CE/LVD EN60950, FCC Part 15 Class B, RoHS
Warranty	3 years, lifelong maintenance.


### Network Management Features

Interface	<p>IEEE802.3X (Full-duplex)</p> <p>Port temperature protection setting</p> <p>Port green Ethernet Energy-saving setting</p> <p>Broadcast storm control based on port speed</p> <p>The speed limit of the message flow in the access port.</p> <p>The minimum particle size is 64Kbps.</p>
Layer 3 Features	<p>L2+ network management ,</p> <p>IPV4/IPV6 management</p> <p>L3 soft routing forwarding,</p> <p>Static route, Default route @ 128 pcs, APR @ 1024 pcs</p>
VLAN	<p>VLAN based on MAC</p> <p>VLAN based on the protocol</p> <p>Voice VLAN, QinQ configuration</p> <p>4K VLAN based on port, IEEE802.1q</p> <p>Port configuration of Access, Trunk, Hybrid</p>
Port Aggregation	LACP, Static aggregation

	Max 18 aggregation groups and 8 ports per group.
Spanning Tree	STP (IEEE802.1d),RSTP (IEEE802.1w),MSTP (IEEE802.1s)
Industrial Ring Network Protocol	G.8032 (ERPS),Recovery time less than 20ms 255 Ring at most, Max 254 devices per ring.
Multicast	MLD Snooping v1/v2,Multicast VLAN IGMP Snooping v1/v2, Max 1024 multicast groups, Fast log out
Port Mirroring	Bidirectional data mirroring based on port
QoS	Flow-based Rate Limiting Flow-based Packet Filtering 8*Output queues of each port 802.1p/DSCP priority mapping Diff-Serv QoS,Priority Mark/Remark Queue Scheduling Algorithm (SP, WRR, SP+WRR)
ACL	Port-based Issuing ACL,ACL based on port and VLAN L2 to L4 packet filtering, matching first 80 bytes message. Provide ACL based on MAC, Destination MAC address, IP Source, Destination IP, IP Protocol Type, TCP/UDP Port, TCP/UDP Port Range, and VLAN, etc.
Security	IP-MAC-VLAN-Port binding ARP inspection,Anti-DoS attack AAA & RADIUS,MAC learning limit Mac black holes,IP source protection IEEE802.1X & MAC address authentication Broadcast storm control,Backup for host datum SSH 2.0,SSL,Port isolation,ARP message speed limit User hierarchical management and password protection
DHCP	DHCP Client,DHCP Snooping,DHCP Server,DHCP Relay
Management	One-key recovery Cable Diagnose,LLDP Web Management (HTTPS)


	<p>NTP, System work log, Ping Test</p> <p>CPU instant utilization status view</p> <p>Console/AUX Modem/Telnet/SSH2.0 CLI</p> <p>Download &amp; Management on FTP, TFTP, Xmodem, SFTP, SNMP</p> <p>V1/V2C/V3</p> <p>ONV NMS - smart network management system platform(LLDP+SNMP)</p>
System	<p>Category 5 Ethernet network cable</p> <p>Web browser: Mozilla Firefox 2.5 or higher, Google browser chrome V42 or higher, Microsoft Internet Explorer10 or later;</p> <p>TCP/IP, network adapter, and network operating system (such as Microsoft Windows, Linux, or Mac OS X) installed on each computer in a network</p>

## DIMENSION



- A. Working Indicate
- B. 8\*10/100/1000M Ethernet Ports
- C. 24\*10/100/1000M SFP Ports
- D. 4\*10/100/1000M SFP Ports
- E. Console Port
- F. Power Input Port AC100-240V, 50/60Hz

## APPLICATION



## ORDERING INFORMATION

Model	Description
700652	L2+ managed Ethernet fiber switch with 8* 10/100/1000M RJ45 ports and 28*100/1000M SFP ports. Built-in 60W power supply. Support 1U/19 inch rack installation.
700654	L2+ managed Ethernet aggregation /core fiber switch with 8* 10/100/1000M RJ45 ports and 24*100/1000M SFP ports and 4*1/10G SFP+ fiber slot ports. Built-in 60W power supply. Support 1U/19 inch rack installation.

**Note:** The SFP optical module is not included by default and needs to be purchased separately.

## PACKING LIST

PACKING LIST	CONTENT	QTY	UNIT
	36-port gigabit managed Ethernet fiber switch	1	SET
	AC Power Cable	1	PC
	RJ45-DB9 Line	1	PC
	Mounting Kits(Hanging Ear)	1	SET
	User Guide	1	PC
	Warranty Card	1	PC

# VandalVeto

5 Korazin st., 5358305 Givataim

Tel: 972-3-5713004 Fax: 972-3-5711450

email: [egber@egber.com](mailto:egber@egber.com)

[www.egber.com](http://www.egber.com)